

Multi-WAN Gigabit VPN Router GWN7002



Kode : GWN7002
Kategori : Grandstream
Harga : Rp 1.131.532,00

The GWN7000 Series are Multi-WAN Gigabit VPN routers with built-in firewalls that allow businesses to build comprehensive wired, wireless and VPN networks for one or many locations. The GWN7002 include 2x 2.5 Gigabit SFP ports, 4x Gigabit ethernet ports (2x PoE output ports) that allow them to provide power to other endpoints.

- Built-in VPN support allows easy access to corporate networks for remote employees
- Multiple WAN ports with load balancing and failover to maximize connection reliability
- Rich firewall features including DDNS, port forwarding, DMZ, UPnP, Anti-Dos, traffic rules, NAT and ALG
- Supports application/protocol monitoring and traffic statistics with Deep Packet Inspection (DPI)
- Advanced QoS to ensure real-time performance of low-latency applications. Supports application, URL, DNS, and web content filtering to block access from unsecure contents



Specification

Model	GWN7002
CPU	Dual ARM Cortex A53 1GHz
Memory and NAT Sessions	256MB RAM, 256MB Flash, 30K NAT sessions
Network Interfaces	2x 2.5 Gigabit SFP ports and 4x Gigabit Ethernet ports *All ports support WAN/LAN configurable
NAT Throughput	2.2Gbps
IPsec VPN Throughput	530Mbps
Auxiliary Ports	1x USB 2.0 port, 1x Reset Pinhole
Mounting	Desktop and wall mounting
LEDs	8 x single-color LEDs for device tracking and status indication
Connection Type	DHCP, Static IP, PPPoE, PPTP, L2TP

Network Protocols	IPv4, IPv6, IEEE802.1Q, IEEE 802.1p, IEEE802.1x, IEEE802.3, IEEE 802.3u, IEEE 802.3x, IEEE802.3ab
Max Concurrent VPN Tunnels	Up to 50 Tunnels
Network Management	GWN7002 embedded controller can manage itself and up to 100 GWN APs <i>GWN.Cloud offers a free cloud management platform for unlimited GWN Routers and GWN APs.</i>
PoE Input	Standard: IEEE 802.3af/at
PoE Output	2x PoE out ports Passive 48V or IEEE802.3af
PoE Power Budget	24V DC 1A: 12.8W 24V DC 1.5A: 24.8W
Power & Green Energy Efficiency	Universal power adaptor included: Input: 100-240VAC 50-60Hz Output: 24V DC 1A (24W)
Environmental	Operation: 0°C to 40°C Storage: -30°C to 60°C Humidity: 10% to 90% Non-condensing
Physical	Unit Dimension: 210mm(L)x130mm(W)x35mm(H)
Package Content	GWN7002 Router, Universal Power Supply, Network Cable, Quick Installation Guide
Compliance	FCC, CE, RCM, IC, UKCA

[Download Datasheet](#)

* Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat

URL : <https://www.citraweb.com/produk/1080/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com