

Managable NetProtector 8P-1U



Kode : MNP8P-1U
Kategori : NetProtector
Harga : Rp 1.800.000,00
Rp 2.600.000,00

8 Port POE yang bisa dicontrol (manageable power on/off), sekaligus proteksi dari petir (Protects an Ethernet data port from damaging surges). **Termasuk dengan Adaptor 24v-5A.**

NetProtector bukan sebuah switch, tetapi sebagai pengganti POE + Surge Arrester :



Netprotect Manageable PoE 8 port, sebuah perangkat tambahan yang sangat berguna di instalasi jaringan wireless.

Fitur :

- PoE adapter functionality
- restarter functionality
- built-in netprotector protects up to 8 devices
- management via www
- all ports shielded
- standard power socket DC 2.1/5.5
- Watchdog
- solid, sleek, all-aluminium, black painted desktop case



Dengan bantuan Adaptor 24volt - 5A yang sudah termasuk didalam paket pembelian, maka NetProtector bisa memberikan catudaya ke 8 perangkat wireless sekaligus.



Fitur Manageable, memungkinkan Administrator jaringan manage power PoE yang digunakan.

Home Relays Watchdog Measurements Settings Logout

DEFAULT SETTINGS

REBOOT

IP ADDRESS of Netprotector PoE

192 . 168 . 0 . 100

MASK ADDRESS

0 . 0 . 0 . 0

GATE ADDRESS

0 . 0 . 0 . 0

MAC

70b3d536d06d

Mode (DHCP 0; Static 1):

NEW password (length min:2, max:6):

Submit

Home Relays Watchdog Measurements

Save names

REL1		RESET
REL2		RESET
REL3		RESET
REL4		RESET
REL5		RESET
REL6		RESET
REL7		RESET
REL8		RESET

Home	Relays	Watchdog	Measurements	Settings	Logout
Parameter		Value			
Power Supply:		13.76344			
Temp 1:		No sensor			
Temp 2:		No sensor			

Specification :

- Input voltage range : 9-30V
- LAN ports : 8 x 10/100Mbps
- LAN & PoE ports : 8 x 10/100Mbps
- LAN/console ports : 1 x 10Mbps
- Power socket : DC 2.1/5.5
- Watchdog : yes, up to 8 entries
- M6 mounting screw : 4 pcs
- Max voltage : 30V
- Max current : 11A
- Weight : 1.5 kg

Signal Path - pairs 1-2, 3-6 :

Rated Voltage : 5V

Maximum Voltage UC : 6V

Protection level line-line UP : $\leq 40V - 1\text{ kV} / \text{ms}$, C3

Protection level line-PG UP : $\leq 600V - 1\text{ kV} / \text{ms}$, C3

Nominal discharge current iN line-line : 20A - 10 / 1000 μs , C3

Nominal discharge current iN line-PG. : 20A - 10 / 1000 μs , C3

Track Supply - lines 4, 5 and 7, 8 :

Rated Voltage : 30V

Maximum Voltage UC : 36V

Nominal Current IN : 400mA

Nominal Discharge current iN line-line : 10 A - 10 / 1000l's, C3

Nominal Discharge current iN line-PG. : 2kA - 8 / 20 μs , C2

Protection Level line-line UP : $\leq 95V - 1\text{ kV} / \text{ms}$, C3

Protection level line-PG UP : $\leq 1000V - 1,2 / 50\mu\text{s}$, C2

** Harga, spesifikasi, dan ketersediaan bisa berubah dan tidak mengikat*

URL : <https://www.citraweb.com/produk/397/>

Informasi lebih lanjut, pemesanan dan pembelian, hubungi: 0274-554444 atau email sales@citraweb.com